



Publication number : **0 490 850 A1**

⑫

EUROPEAN PATENT APPLICATION

⑫ Application number : **91850297.2**

⑤ Int. Cl.⁵ : **B25D 17/04**

⑫ Date of filing : **29.11.91**

③ Priority : **11.12.90 SE 9003947**

④ Date of publication of application :
17.06.92 Bulletin 92/25

⑧ Designated Contracting States :
DE FR GB IT SE


⑦ Applicant : **ATLAS COPCO TOOLS AB,
STOCKHOLM
P.O. Box 90111
S-120 21 Stockholm (SE)**

⑦ Inventor : **Holmin, Mats Cornelius
3, Fredhällsgatan
S-112 34 Stockholm (SE)
Inventor : Olsson, Sten Herman
10, Mittelvägen
S-122 32 Enskede (SE)
Inventor : Skogsberg, Lars Torbjörn
5, Klevbergsvägen
S-179 00 Stenhamra (SE)**

⑦ Representative : **Pantzar, Tord
Atlas Copco Tools AB Patent Department Box
90111
S-120 21 Stockholm (SE)**

⑤ **Vibration Insulated power tool handle.**

⑤ A vibration insulated power tool handle, comprising a tubular grip portion (10), a mounting means (11) for rigid mounting on a tool housing, and an elastic vibration insulating leaf spring membrane (12) interconnecting the grip portion (10) and the mounting means (11). The spring membrane (12) is formed with a central opening (19) for receiving a screw (21) of the mounting means (11) and is connected by its periphery to a socket portion (16) on the grip portion (10).



This invention relates to a vibration insulated power tool handle of the type having a grip portion, a mounting means for rigid mounting on the tool housing, and an elastic vibration insulating member interconnecting the grip portion and the mounting means.

The basic problem to be solved by the invention is how to effectively protect the operator from the hazardous vibrations developed in power tools like grinding machines. Previous attempts to solve this problem have been made, and most of them have comprised handles with some kind of vibration insulating elastic elements.

Most of these known handles have provided grip means which have offered an acceptable vibration insulation. They have all failed, however, to combine a good vibration insulation with a safe and comfortable handling of the tool and a compact design.

The object of the invention is to create a power tool handle which not only provides a good vibration insulation but a safe and comfortable handling of the tool and a design that does not add to the length of the handle.

A preferred embodiment of the invention is described below in detail with reference to the accompanying drawing.

On the drawing,

Fig 1 shows a longitudinal section through a handle according to the invention.

Fig 2 shows an end view of the handle in Fig 1.

The handle shown in the drawing figures is suitable for use on for instance a rotation grinding machine, pneumatic or electric, and comprises a grip portion 10, a mounting means 11 and a vibration insulating spring element 12.

The grip portion 10 comprises a rigid inner tube 14 and a resilient outer grip sleeve 15 of for instance rubber. At its one end, the inner tube 14 has a bell shaped socket 16, and at its opposite end it receives the stem portion 17 of an inertia element 18. The purpose of the latter is to lower the resonance frequency of the handle.

The vibration insulating spring element 12 comprises a somewhat conical steel disc or membrane which is snapped by its periphery into a circumferential groove 20 in the bell shaped socket 16. The steel membrane 12 is formed with a central opening 19 through which the mounting means 11 extends. The latter comprises a screw 21 with an internal hexagon head, a stepped washer 22 and a nut 27. The latter also serves as a distance piece relative to the tool housing.

A characteristic feature of the membrane type spring element 12 is that it is completely non-resilient to radially acting forces, i.e. forces acting transversely to the handle at the mounting end of the latter. Transverse forces applied on the handle at a distance from the membrane 12, however, cause elastic bending deformations of the latter. By its somewhat conical



shape, the spring membrane 12 is apt not to yield too easily to axial forces, which means that the handle offers a precise control of the tool.

The spring characteristic of the steel membrane 12 and the mass of the inertia element 18 are adapted to the working frequency e.g. the rotation speed, of the tool such that the handle has a resonance frequency that is well below the working frequency of the tool.

Although the above described embodiment of the invention comprises a disc shaped steel membrane having its central part connected to the mounting means and its periphery connected to the handle tube it is to be noted that the invention also includes the opposite arrangement where the mounting means is connected to the periphery of the steel membrane and the handle tube to the central part thereof.

Claims

1. Vibration insulated power tool handle, comprising a grip portion (10), a mounting means (11) for rigid mounting on a tool housing, and an elastic vibration insulating member (12) interconnecting said grip portion (10) and said mounting means (11), characterized in that said vibration insulating member (12) comprises a substantially disc shaped leaf spring element which is connected at its centre to one of said mounting means (11) and said grip portion (10) and at its periphery to the other one of said mounting means (11) and said grip portion (10).
2. Handle according to claim 1, wherein said grip portion (10) is substantially cylindrical, and said spring element (12) is located in a plane substantially transverse to the length axis of said grip portion (10).
3. Handle according to claim 1 or 2, wherein said mounting means (11) comprises a screw (21) extending through a central opening (19) in said spring element (12), and said grip portion (10) comprises a bell shaped socket portion (16) formed with an internal circumferential groove (20) for cooperation with the outer periphery of said spring element (12).
4. Handle according to anyone of claims 1-3, wherein said grip portion (10) is tubular and formed in one piece with said socket portion (16).
5. Handle according to anyone of claims 1-4, wherein said grip portion (10) at its free end is provided with an inertia element (18) for lowering the resonance frequency of the handle.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 91 85 0297

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	DE-U-9 004 091 (METABOWERKE) * claim 1; figures *	1	B25D17/04
A	US-A-4 282 938 (MINAMIDATE) * column 3, line 67 - column 4, line 24; figures *	1	
A	DE-A-3 304 849 (MINAMIDATE) * abstract; figures *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl.5) B25D B25G B25F
Place of search THE HAGUE		Date of completion of the search 20 MARCH 1992	Examiner WEIAND T.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1501 (03.92) (P0001)